

DECOPRIMER®

Decorative Plaster Primer

DESCRIPTION

Acrylic dispersion based, single-component, white colored, waterborne **primer** with high covering properties which can be used under all cement-based interior and exterior cladding materials.

APPLICATION AREAS

- Indoor and outdoor
- Horizontal and vertical applications
- For increasing adherence prior to the application of decorative plasters on thermal insulation board plasters
- As a primer before applications on old surfaces
- Under all cement based interior and exterior facade coating materials.

TECHNICAL PROPERTIES

Appearance	White colored, acrylic based dispersion
Density	~ 1.55 kg/L
Application Temperature	Between +5°C and +35°C
Drying Time	~ 6 hours
Service Temperature	-30°C / +80°C

ADVANTAGES

- Provides high adherence between the surface and the coating mortar
- Prevents the mortar to lose its water fast when applied prior to cement based coatings on absorbent surfaces
- Provides resistance to moisture
- Has covering power.
- Ready to use, easily and quickly applied.
- Waterborne, odorless, and safe to use indoor.
- Easy to apply with its white color in thermal insulation applications.

CONSUMPTION

100 - 300 g/m² (Varies depending on the application surface.)

APPLICATION

PREPARATION OF THE SURFACE

- The surface must be cured.
- The surface must be clear of materials which prevent bonding, such as dust, oil, tar, bitumen, paint, silicone, curing agents, detergents and mold release oils.

APPLICATION

- DECOPRIMER Decorative Plaster Primer is ready-to-use. Stir well before use and apply single layer to the surface with a brush or roller.
- If necessary, it can be diluted with clean water at a maximum of 5% by weight.
- Drying time of the product is about 6 hours.

CAUTION

- Avoid application in temperatures below +5°C and above +35°C.
- Avoid application on frozen areas, on areas under risk of freezing in 24 hours or on areas open to direct sunlight or wind.
- Protect the surface from rain.
- Extremely hot surfaces can be moistened before application.
- Close the package cover tightly when not in use.
- Do not add foreign substances to the product.

PACKAGING

15 kg plastic buckets

SHELF LIFE

Unopened packages can be stored for 12 months in a dry environment between +5°C and +25°C. Shake well before use. Protect against freezing.

HEALTH AND SAFETY

As with all chemical products, avoid contact with food products, skin, eyes and mouth during use and storage. During the application, use work clothes, protective gloves and glasses in accordance with the occupational and worker health rules. Consult a doctor if accidentally swallowed. In case of contact with skin, rinse with water. Do not leave the cover open. Avoid prolonged contact with uncured silicone. Store out of the reach of children.

The application instructions and technical values given for the products have been obtained in accordance with our tests and experiences in accordance with international standards at 23±2°C temperature and 50±5% relative humidity conditions. These values may vary depending on ambient conditions. High temperatures shorten the times, low temperatures lengthen them. Before starting the application, the user should test whether the product is suitable for the application and purpose. FIXA Yapı Chemicals San. Trade Ltd. Sti. is not responsible. This Technical Data Sheet remains valid until the next revision is published. FIXA reserves the right to change the values specified in this Technical Data Sheet, provided that the new version is published. It is the user's responsibility to check that the document is up-to-date. Please contact our sales department