

FIXA®

Stain Remover

DESCRIPTION

Liquid cleaner with **base content** to remove stains such as oil, coffee, tea from covering materials.

APPLICATION AREAS

- Indoor and outdoor
- Horizontal and vertical surfaces
- Glossy or matte surfaces
- Parquet and laminated parquet floors
- Removing stubborn stains such as oil, coffee, tea, ink, wine and fruit juices from covering materials, such as ceramic, granite ceramic, clinker, cotto, natural stone, marble and granite.

TECHNICAL PROPERTIES

Appearance	Light pink transparent liquid
Liquid Density	0.98 - 1.00 kg/L
Application Temperature	Between +5°C and +35°C
pH	~ 13

ADVANTAGES

- Can be conveniently used on sensitive surfaces due to its base content
- Can be used by spreading on the whole surface
- Its active components are 90% recyclable.

CONSUMPTION

Varies depending on the amount of residues on the surface.
20 - 100 m² of surface can be cleaned with 1 L product.

PACKAGING

1 L plastic bottles

APPLICATION**APPLICATION**

- Wipe the surface with a wet cloth before application.
- Depending on the amount of stain, dilute the product with water at a ratio of 1/1 to 1/5. Diluted product can be applied to the surface in 2 ways:

Manual Cleaning: Spread FİXA Stain Remover with a brush over a 2 m² area to be cleaned. Wait 2 - 3 minutes for the product to penetrate the surface and wipe off the dirty liquid on the surface with a cloth. After the entire area is cleaned, if necessary, apply a second coat of FIXA Stain Remover by diluting it with less water and spread it directly on the stains and dirt. Wipe the surface with water again and rinse.

Cleaning with the Machine: Spread FİXA Stain Remover with a brush over a 4 m² area to be cleaned. Wait for 2 - 3 minutes to allow the product to penetrate the surface and wipe off the dirty liquid on the surface by rubbing with the machine. After the entire area is cleaned, if necessary, apply a second coat of FİXA Stain Remover by diluting it with less water and spread it directly on the stains and dirt. Wipe the surface with water again and rinse.

CAUTION

- **Use gloves.**
- Do not use on laminate flooring, unglazed ceramics, unpolished parquet surfaces and glass surfaces without diluting with water.
- Do not use on aluminum surfaces or objects.
- Do not add other cleaning materials and bleaches into the product.
- Avoid contamination of drinking water and groundwater.

SHELF LIFE

Expires in 12 months. Store unopened packages in a dry environment. Shake well before use. Protect against freezing.

HEALTH AND SAFETY

As with all chemical products, avoid contact with food, skin, eyes and mouth during use and storage. In case of contact immediately wash with plenty of water and soap. If accidentally swallowed, drink water, do not try to neutralise and immediately consult a doctor. Do not induce vomiting. During the application, use work clothes, protective gloves and glasses in accordance with the occupational and worker health rules. Avoid contact with food and drinks, ventilate application area. Store out of the reach of children.

The application instructions and technical values given for the products have been obtained in accordance with our tests and experiences in accordance with international standards at 23±2°C temperature and 50±5% relative humidity conditions. These values may vary depending on ambient conditions. High temperatures shorten the times, low temperatures lengthen them. Before starting the application, the user should test whether the product is suitable for the application and purpose. FIXA Yapı Chemicals San. Trade Ltd. Sti. is not responsible. This Technical Data Sheet remains valid until the next revision is published. FIXA reserves the right to change the values specified in this Technical Data Sheet, provided that the new version is published. It is the user's responsibility to check that the document is up-to-date. Please contact our sales department for more information.