

FIXA[®]

Tile Grout Cleaner

DESCRIPTION

Liquid cleaner with **acidic content** to remove stains and dirt accumulated in tile grouts and joints of covering materials.

APPLICATION AREAS

- Indoor and outdoor
- Horizontal and vertical surface
- Tile grouts and joints of opaque covering materials
- Since it is acidic and abrasive, a tape must be used to prevent spills over the sides of grouts when working on glossy covering materials.

TECHNICAL PROPERTIES

Appearance	Light green transparent liquid
Liquid Density	1.00 - 1.10 kg/L
Application Temperature	Between +5°C and +35°C
pH	~ 1

ADVANTAGES

- Cleans easily the residues that cannot be removed with regular cleaning materials thanks to its acidic content
- Its active components are 90% recyclable.

CONSUMPTION

Varies depending on the amount of dirt on the surface and the width of grout.

PACKAGING

500 ml spray packages

APPLICATION**PREPARATION OF THE SURFACE**

- Since the material has an acidic structure, check the resistance of the surface to acid before the application by making a test in a small area. In such cases, cover the joint edges with tape to prevent the coating material to be damaged.
- Before the application, clean the surface mechanically and remove the dust.

APPLICATION

- Do not dilute FIXA Tile Grout Cleaner.
- Turn the spray nozzle on, spray the product on the dirty area.
- Wait 1 - 2 minutes for the material to penetrate the surface. Then clean the joint gaps by pressing with a suitable brush or cloth.
- When the cleaning is finished, rinse the surface with water.

CAUTION

- **Use acid resistant gloves.**
- Use only between the joints and do not spread on ceramic and tile surfaces.

- Avoid contact with metals. Not suitable for acid-affected surfaces such as acrylic and wood.
- When using on non-acid resistant coating materials, polished and buffed surfaces and polished marble and granite surfaces, use tape to prevent spillage beyond the joint gaps.
- Do not add other cleaning materials and bleaches into the product.
- Avoid contamination of drinking water and groundwater.

SHELF LIFE

Expires in 12 months. Store unopened packages in a dry environment. Shake well before use. Protect against freezing.

HEALTH AND SAFETY

As with all chemical products, avoid contact with food, skin, eyes and mouth during use and storage. In case of contact immediately wash with plenty of water and soap. If accidentally swallowed, drink water, do not try to neutralise and immediately consult a doctor. Do not induce vomiting. During the application, use work clothes, protective gloves and glasses in accordance with the occupational and worker health rules. Avoid contact with food and drinks, ventilate application area. Store out of the reach of children.

The application instructions and technical values given for the products have been obtained in accordance with our tests and experiences in accordance with international standards at 23±2°C temperature and 50±5% relative humidity conditions. These values may vary depending on ambient conditions. High temperatures shorten the times, low temperatures lengthen them. Before starting the application, the user should test whether the product is suitable for the application and purpose. FIXA Yapı Chemicals San. Trade Ltd. Sti. is not responsible. This Technical Data Sheet remains valid until the next revision is published. FIXA reserves the right to change the values specified in this Technical Data Sheet, provided that the new version is published. It is the user's responsibility to check that the document is up-to-date. Please contact our sales department for more information.